



FONTAINE®

Velocity™

FLATBED AND
DROPDECK TRAILERS
BUILT FOR THE
CANADIAN ROAD



WWW.FONTAINETRAILER.COM

YOU ALWAYS GET MORE FOR YOUR MONEY WITH FONTAINE VELOCITY TRAILERS



- STRUCTURAL STEEL SIDERAILS AND STEEL FRONT AND REAR SKIRT FOR HEAVY-DUTY PERFORMANCE
- ALL LIGHTS ARE LED TYPE WITH FIVE MARKER LIGHTS PER SIDE INCLUDING MID-TURN SIGNALS AND SIX LIGHTS ON THE REAR PLUS A CENTRAL REAR BAR LIGHT FOR ADDED SAFETY
- AIR LINES AND ELECTRICAL HARNESS RUN DOWN THE CENTER OF THE TRAILER FOR EASY ACCESS AND MAXIMUM PROTECTION FROM ROAD DEBRIS, SNOW AND ICE



- 3-BAR WINCHES MAKE LOAD SECUREMENT FAST AND EASY
- CONSPICUITY TAPE IS FASTENED TO A RECESSED AREA OF THE RUBRAIL FOR BETTER ADHESION AND ATTRACTIVE APPEARANCE



- 1 1/8" WOOD DECK IS STEEL REINFORCED WITH I-BEAM CROSSMEMBERS ON 12" CENTERS FOR ADDED STRENGTH
- SPECIAL J HOOKS LOCATED OPPOSITE WINCHES FOR GREATER CONVENIENCE
- TARP HOOKS LOCATED EVERY 2' ON ALL SIDES WHERE APPROPRIATE



- STRONGEST MAIN BEAM IN THE INDUSTRY FEATURES GRADE 130 FLANGES (TOP AND BOTTOM) WELDED ON BOTH SIDES FOR STRUCTURAL INTEGRITY
- STEEL REINFORCED FRAME PROVIDES GREATER STABILITY FOR SINGLE COIL HAULING
- CHANGING AXLE POSITIONS IS FAST AND EASY TO GIVE YOU THE ULTIMATE IN FLEXIBILITY AND CONVENIENCE



FONTAINE®

Velocity™



FIND OUT WHY FONTAINE IS THE LARGEST PLATFORM TRAILER MANUFACTURER IN THE WORLD.

SEE OUR COMPLETE LINE OF STEEL, ALUMINUM AND COMBINATION TRAILERS FOR FLATBED, DROPDECK/STEPDECK AND LOWBED/ MACHINERY CUSTOMERS AT YOUR NEARBY FONTAINE DEALER, OR VISIT OUR WEBSITE TODAY: WWW.FONTAINETRAILER.COM.

YOU ALWAYS GET MORE FOR YOUR MONEY WITH FONTAINE!

A I N E T R A I L E R . C O M

VELOCITY PLATFORM™ SPECIFICATIONS

	VELOCITY 53' DROPDECK/STEPDECK	VELOCITY 48' SLIDING SPRING TANDEM	VELOCITY 53' SLIDING AIR TRIDEM
OVERALL LENGTH / WIDTH	53' x 102"	48' x 102"	53' x 102"
SUSPENSION TYPE	Tri-axle	Sliding spring tandem	Sliding air tridem
DECK LENGTHS	11' front, 42' rear	48'	53'
FRAME RATING	80,000 lbs distributed		
LOADED DECK HEIGHT	49" front and 40" rear	49"	49"
FLOORING	1 1/8" wood, continuous floor		
CROSSMEMBERS	18" centers front deck, 12" centers rear deck 4" jr. I-steel	12" centers entire deck 4" jr. I-steel	12" centers entire deck 4" jr. I-steel
SIDE RAILS	6" structural channel @ 6.5 lbs/ft Full length on rear deck	6" structural channel @ 6.5 lbs/ft Full length	6" structural channel @ 6.5 lbs/ft Full length
STAKE POCKETS	3/16" steel on 48" centers	3/16" steel on 24" centers	3/16" steel on 48" centers
PIPE SPOOLS	Between stake pockets		
RUBRAIL	2 1/2" rolled formed steel		
MAIN BEAMS	Minimum grade 130 flanges welded on both sides of the web		
KINGPIN	18"	30"	24"
LOADED FIFTH WHEEL HEIGHT	49"		
LANDING GEAR	Fontaine 2-speed		
KNEE BRACES	Fabricated on approximately 60" centers		
BULKHEAD POCKETS	-	4 - F-5 DOT-type steel	-
NUMBER OF AXLES	3 Intraax	2	3
AXLE SPINDLE	Tapered		
DUST SHIELD	Dust shields installed on all axles		
BRAKES	Spring brakes, auto slacks		
ABS	4S/2M, no cable or tool		
AXLE SPREAD	60", kingpin to center axle 40' 10 7/8"	49"	60"
HUB AND DRUMS	10-hole, hub-piloted with outboard cast drums		
WHEEL ENDS	Grease in hubs ***** 5-year wheel end warranty *****		
WHEELS	22.5 x 8.25 steel disc wheels, pre-painted white		
TIRES	255/70R 22.5 16PR	295/75R 22.5 14PR	295/75R 22.5 14PR
TIRE BRAND	OEM standard		
SUSPENSION DETAIL	Hendrickson AA230L Intraax air ride	Hutch H-9700 3-leaf spring slider 60" adjustable	Hendrickson tri axle sliding system
DUMP VALVE	Manual dump valve, liquid filled gauge in box	-	Manual dump valve, liquid filled gauge in box
FRONT CORNERS	Tapered		
ELECTRICAL SYSTEM	LED: 5 lights on each side including front corner, 6 lights on rear plus a central rear bar light		
PAINT	Black urethane with Velocity decals		
CONSPICUITY TAPE	Per NHTSA specifications, installed in recess on rubrails		
BUMPER	Bolt-on type, meets underride requirements		
MUDFLAPS	1 set Velocity with bolt-on mud flap bracket	1 set Velocity	1 set Velocity
SPARE TIRE CARRIER	1 standard, between lower gooseneck beams	optional	optional
SIDE MOUNTED WINCHES	26 standard, without straps 13 per side, three bar type	18 standard, without straps 9 per side, three bar type	26 standard, without straps 13 per side, three bar type
SPECIAL J HOOKS	26 total, 13 per side, located opposite winches	18 total, 9 per side, located opposite winches	26 total, 13 per side, located opposite winches
TARP HOOKS	2' centers on all sides where possible, undermount rs/cs, side mount front/back		
DOCK BUMPERS	1 pair rubber on rear		
VIN PLATE	Canadian		
WEIGHT	14,438 lbs +/- 3%	12,215 lbs +/- 3%	14,487 lbs +/- 3%



Specifications subject to change without notice.
Photos may show some optional equipment.



Fontaine Trailer Company

430 Letson Road • P.O. Box 619 • Haleyville, AL 35565 • 800-821-6535 • fax 205-486-8985 • www.fontainetrailer.com