



UNBEATABLE QUALITY

BUILT YOUR WAY

OUR PRODUCT LINE

CUSTOMER SERVICE

Dump Bodies

Trailers

Specialty

In-Stock New & Used

Distributors

HCX

HR

LDC

LWC

MDC

MH

MH EVO

ROH

SE

SSD

UltraLight

▲ Take a look at all of our dump bodies. ▲

DYNA HAULER®/MH



MATERIAL HAULER DUMP BODY

Whether you choose steel or aluminum, you can rely on the rugged **DYNA**^{HAULER/MH} for all your material hauling needs. These precision-engineered truck bodies are built to withstand many years of hard material hauling use and come with many extra, ready-to-work features. Just some of these standard features include a full length and full width cab protector, a wear-resistant 3/16" floor, dirt shedding catwalk with inside cleaner plate, side mounted hydraulic tanks, and heavy-duty steps and ladders, sideboards. **DYNA**^{HAULER/MH} is one of our most popular models.



STANDARD STEEL SPECIFICATIONS:

Build to any length

From 13' to 20'

Cab protector

10 ga., full length/full width, load bearing.

Side Panels

10 ga., 48" high, with 2" x 4" x 1/4" structural tubing top rail and 7" sideboards with center gussets.

Floor

3/16", high-tensile A-572 with .20 copper, full width.

Understructure

4" structural channel cross-members on 12" centers (5.4 lb./ft.). 6" I-beam longitudinals (12.5 lb./ft.). 2" oak mounting strip.

Tailgate

54" high, 3 panel, 8 ga., with offset top hardware.

Hoist

Front mounted, telescopic, with safety prop.

Lighting

Truck-Lite sealed and shock proof system. Body-up light and pto light with premium inside controls.

Paint

Sherwin Williams Genesis.

Other standard features

Dirt shedding catwalk with inside cleaner plate. Side mounted hydraulic tank. Ladder & steps. Tailgate chains. Tarp rods.

POPULAR STEEL OPTIONS:

Sides

42", 54", 60", 66" height. 8 ga., 3/16", 1/4" thickness. High tensile or Hardox 400.

Floors

1/4", 3/8", 5/16". High tensile or Hardox 400. Cushion floors available.

Understructure

I-beam cross members. Rubber mounting strip.

Tailgate

6 or 9 panel. 6" or 8" sloped. Air operated and barn door type gates available.

Hoist

Front mount, twin telescopic, triple hoist, or trunnion mount telescopic hoist.

Other

Spreader apron. Horizontal side braces. Air operated and premium Chelsea pto. Body heat. Tarp systems. Tool box. Coal doors. Pintle hook.

STANDARD ALUMINUM SPECIFICATIONS:

Build to any length

from 13' to 20'

Cab protector

3/16", full length/full width, load bearing.

Side Panels

3/16" 5454-H34, 54" high, with 4" x 4" 6061-T6 extruded top rail and 7" sideboards with center gussets.

Floor

1/4", 5454-H34.

Understructure

4" I-beam cross members on 12" centers, 2.70# per ft. 6" I-beam longitudinals, 5.10# per ft. 2" extruded rubber mounting strip.

Tailgate

60" high, 3 panel, 1/4", with offset top hardware.

Hoist

Front mounted, telescopic, with safety prop.

Lighting

Truck-Lite sealed and shock proof system. Body-up light and pto light with premium inside controls.

Other standard features

Dirt shedding catwalk with inside cleaner plate. Side mounted hydraulic tank. Ladder & steps. Tailgate chains. Tarp rods.

POPULAR ALUMINUM OPTIONS:

Sides

42", 48", 60", 66" height. 1/4", 5/16" thickness.

Floors

3/8", 5/16", 1/2". Cushion floors available.

Tailgate

48", 54", 66", 72". 6" or 8" sloped. Air operated and barn door type gates available.

Hoist

Front mount, twin telescopic, triple hoist, or trunnion mount telescopic hoist.

Other

Spreader apron. Air operated and premium Chelsea pto. Body heat. Tarp systems. Tool box. Coal doors. Pintle hook

Standard specifications may vary according to customer preferences and requirements. At J&J, we custom build to suit your needs.
Licensed under U.S. Patent No. 5,454,620.



Copyright © 2000-2007 Somerset Welding and Steel, Inc. All rights reserved.
J&J Truck Bodies & Trailers is a division of Somerset Welding and Steel, Inc.

JJBodies.com website developed by [Object Red](#).